

# BANNERS (BN)



## PRODUCT FEATURES

- Economical sound absorption
- Excellent sound absorption
- Flexible and adjustable
- Great design potential
- Adds design and color to ceilings
- Popular in large venues, arenas, stadiums, and cafeterias

## CORE

75-1.65 pcf fiberglass  
2" and 4" thick

## SIZES

Up to 4' x 25'  
Intermediate support suggested for  
Banners over 10' long

## MOUNTING

Washers or stiffeners

## EDGES

Natural

## FINISH

Nylon and PVC (with or without  
perforated sides)

## FLAMMABILITY

All components have a Class "A"  
rating per ASTM E84

## SOUND ABSORPTION

### - BN2PP: 2", PVC, Perforated, 1.2 pcf

Hz	125	250	500	1000	2000	4000	NRC
BN2PP	.90	1.06	1.02	1.10	1.15	1.22	1.10

### - BN2PS: 2", PVC, Solid, 1.2 pcf

Hz	125	250	500	1000	2000	4000	NRC
BN2PS	.85	1.04	1.03	1.06	.69	.42	.95

### - BN2N: 2", Nylon, 1.65 pcf

Hz	125	250	500	1000	2000	4000	NRC
BN2N	.83	1.02	1.00	1.04	.64	.39	.95

### - BN4PP: 4", PVC, Perforated, .75 pcf

Hz	125	250	500	1000	2000	4000	NRC
BN4PP	1.31	1.11	1.14	1.17	1.15	1.19	1.15

For best sound absorption, perforated sides should be installed facing the floor.