

ACOUSTI-PANELS (AP) WALL PANELS



PRODUCT FEATURES

- Economical wall panel
- Excellent sound absorption
- Durable enough for a gym
- Custom shapes and sizes
- Fabric finish
- Available in a variety of thicknesses

CORE

6 - 7 pcf fiberglass
1/2" - 4" thick

SIZES*

Up to 4' x 12' and 5' x 10'

*Some size restrictions apply, [see website](#)

MOUNTING

Adhesive, impaling clips,
two-part Z-clips

EDGES

Square, beveled, radiused and
hardened

FINISH

Fabric finish

FLAMMABILITY

All components have a Class "A"
rating per ASTM E84

SOUND ABSORPTION

Hz	125	250	500	1000	2000	4000	NRC
AP .5	.07	.09	.35	.77	.98	1.03	.55
AP .75	.04	.19	.59	.91	1.05	1.02	.70
AP 1	.10	.25	.84	1.08	1.13	1.11	.85
AP 1.5	.31	.58	1.03	1.10	1.05	1.04	.95
AP 2	.42	.89	1.12	1.07	1.10	1.09	1.05
AP 3	.75	.89	1.11	1.21	1.21	1.20	1.10
AP 4	.87	.87	1.24	1.26	1.26	1.25	1.15

Note: NRC test results based on our standard acoustically transparent fabric. Results may vary with other fabrics.

CONTROLLING SOUND BEAUTIFULLY

800-737-0307 • 636-225-8800
gsacoustics.com

