

# BANNERS (BN)



## PRODUCT FEATURES

- Economical sound absorption
- Excellent sound absorption
- Flexible and adjustable
- Great design potential
- Adds design and color to ceilings
- Popular in large venues, arenas, stadiums, and cafeterias

## CORE

.75-1.65 pcf fiberglass  
2" and 4" thick

## SIZES

Up to 4' x 25'  
Intermediate support suggested for  
Banners over 10' long

## MOUNTING

Washers or stiffeners

## EDGES

Natural

## FINISH

Nylon and PVC (with or without  
perforated sides)

## FLAMMABILITY

All components have a Class "A"  
rating per ASTM E84

## SOUND ABSORPTION

### - BN2PP: 2", PVC, Perforated, 1.2 pcf

| Hz    | 125 | 250  | 500  | 1000 | 2000 | 4000 | NRC  |
|-------|-----|------|------|------|------|------|------|
| BN2PP | .90 | 1.06 | 1.02 | 1.10 | 1.15 | 1.22 | 1.10 |

### - BN2PS: 2", PVC, Solid, 1.2 pcf

| Hz    | 125 | 250  | 500  | 1000 | 2000 | 4000 | NRC |
|-------|-----|------|------|------|------|------|-----|
| BN2PS | .85 | 1.04 | 1.03 | 1.06 | .69  | .42  | .95 |

### - BN2N: 2", Nylon, 1.65 pcf

| Hz   | 125 | 250  | 500  | 1000 | 2000 | 4000 | NRC |
|------|-----|------|------|------|------|------|-----|
| BN2N | .83 | 1.02 | 1.00 | 1.04 | .64  | .39  | .95 |

### - BN4PP: 4", PVC, Perforated, .75 pcf

| Hz    | 125  | 250  | 500  | 1000 | 2000 | 4000 | NRC  |
|-------|------|------|------|------|------|------|------|
| BN4PP | 1.31 | 1.11 | 1.14 | 1.17 | 1.15 | 1.19 | 1.15 |

For best sound absorption, perforated sides should be installed facing the floor.

CONTROLLING SOUND BEAUTIFULLY

800-737-0307 • 636-225-8800  
gsacoustics.com

