

ACOUSTI-PANELS CEILING (APC)



PRODUCT FEATURES

- Durable, high-sound absorption
- Attached to metal deck in open ceiling designs
- Finishes: fabric, paint, custom printed and white or black texture
- Custom sizes and shapes

CORE

6 - 7 pcf fiberglass
1" - 4" thick

SIZES

Direct Mount: up to 4' x 8'
Lay-In: up to 5' x 5'
Classic White: up to 4' x 8'
Classic Black: up to 3' 6" x 8'

EDGES

Square, beveled, micro-bevel (for adjoined panels), radiused.

FINISH

Fabric, paint, custom printed and white or black texture

FLAMMABILITY

All components have a Class "A" rating per ASTM E84

SOUND ABSORPTION - Direct Mount

Hz	125	250	500	1000	2000	4000	NRC
APC 1	.10	.25	.84	1.08	1.13	1.11	.85
APC 1.5	.31	.58	1.03	1.10	1.05	1.04	.95
APC 2	.42	.89	1.12	1.07	1.10	1.09	1.05

SOUND ABSORPTION - Lay-In Ceiling

Hz	125	250	500	1000	2000	4000	NRC
APC 1	.94	1.00	.80	1.05	1.07	1.15	1.00

Note: NRC test results based on our standard acoustically transparent fabric. Results may vary with other fabrics.

ACOUSTI-PANELS CEILING (APC)



Exceeding design requirements and expectations for acoustical solutions, G&S Acoustics offers custom products and proven mounting systems.

FINISHES



Fabric (APC)

Large variety of fabrics in multiple colors and textures.



Printed - Image (AIC)

Custom printed image on fabric.



Painted - Pinta (PPC)

Sherwin Williams flat acoustical paint. Mold and mildew resistant surface.



Texture - Classic (CC)

White (CCW) or black (CCB) textured finish.

CUSTOMIZATION



Custom Cut

Custom shapes and sizes.

SUSTAINABILITY



27% Pre-Consumer Recycled content and 34% Post-Consumer Recycled content.

Health Product Declaration (HPD) reports available [on-line](#).



MOUNTING



Snap-on Rotofast

for 1" to 2" panels




Clear Puck

Painted option also available



Continuous Hanger Bar (CHB)

with CHB, 1" to 2" Panels



Lay-in Grid

15/16" Ceiling Grid Provided by Others

Customized mounting available.



CONTROLLING SOUND BEAUTIFULLY

800-737-0307 • 636-225-8800

gsacoustics.com

Page 2 of 2