Panel | Acoustic

duvaltex

FR701® 2100





FR701® 2100

Content	100% post-consumer recycled polyester
Weight	16.0 ± 0.5 oz./lin. yd
Width	66" min. useable
Repeat	none

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

Bleach Cleanable - May be cleaned with a 10% bleachto-water solution. Rinse well after cleaning. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Miscellaneous

Application testing of this product is recommended. Colors may vary between dye lots. This is a nondirectional fabric.

Proudly woven in North America supporting our local communities.

Sustainability

100% recycled and recyclable



Performance

Colorfastness to light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours



Colorfastness to crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet



Breaking Strength (ASTM D5034) 150 lbf min. warp and fill



Flammability

ASTM E84 Class I or A

Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

Acoustic Transparency:

95%

For more detailed results, please consult our website.



This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this $\dot{\textbf{U}}.\dot{\textbf{L}}.$ recognized fabric is not required on approved panels from participating manufacturers.



Renowned for its exceptional performance and style, Guilford of Maine has set industry standards in acoustics and panel fabrics for many decades. We present the Guilford of Maine Collection - a selection of timeless fabrics.





