ACOUSTI-PANELS (AP) WALL PANELS

G&S ACOUSTICS
Employee Owned

PRODUCT FEATURES

- Excellent sound absorption
- Economical wall panel
- Available in a variety of thicknesses

- Finishes: fabric, paint, custom printed and white or black texture
- Standard or custom shapes and sizes

CORE

6 - 7 pcf fiberglass
1/2" - 4" thick

SIZES*

Up to 4' x 10'
*Some size restrictions apply, see website

MOUNTING

Adhesive, impaling clips,
two-part Z-clips

EDGES

Square, beveled, radiused

FINISH

Fabric, paint, custom printed and
white or black texture

FLAMMABILITY

All components have a Class "A"
rating per ASTM E84

More details on second page.

SOUND ABSORPTION

Hz	125	250	500	1000	2000	4000	NRC
AP .5	.07	.09	.35	.77	.98	1.03	.55
AP .75	.04	.19	.59	.91	1.05	1.02	.70
AP 1	.10	.25	.84	1.08	1.13	1.11	.85
AP 1.5	.31	.58	1.03	1.10	1.05	1.04	.95
AP 2	.42	.89	1.12	1.07	1.10	1.09	1.05
AP 3	.75	.89	1.11	1.21	1.21	1.20	1.10
AP 4	.87	.87	1.24	1.26	1.26	1.25	1.15

Note: NRC test results based on our standard acoustically transparent fabric. Results may vary with other fabrics.