Melody

mTiles
Ceiling Tiles

G&S ACOUSTICS
Employee Owned

Melody mTiles are **recycled polyester, sound-absorbing ceiling tiles**. mTiles can be installed in a variety of ways, including lay-in grids, direct applied with mechanical fasteners or adhesive. mTiles are available in 5 colors, White in 1" and 2" thick. Colors Black, Silver, Pewter and Khaki available in 1" thick only.

MOUNTING TYPES

Lay-In (MCL)

Melody mTiles

Adhesive (MCA)

Melody mTiles

Trowel applied Adhesive

Puck (MCP)

Anchor (by others)

Puck

Melody mTiles

SOUND ABSORPTION - DIRECT MOUNT TO CEILING (MCA & MCP)

Hz	125	250	500	1000	2000	4000	N.R.C.
MCA-1, MCP-1	.12	.26	.64	.90	1.09	1.12	.70
MCA-2, MCP-2	.32	.66	1.06	1.19	1.20	1.22	1.05

Note: NRC test results based on Type A Mounting.

SOUND ABSORPTION - LAY-IN CEILING (MCL)

Hz	125	250	500	1000	2000	4000	N.R.C.
MCL-1	.92	1.02	.79	.98	1.01	1.13	.95

Note: NRC test results based on E-400 Mounting.

CORE
1" and 2" Recycled Polyester

SIZES
Lay-In: Up to 4' x 4' or 2' x 8'
Adhesive Mount: Up to 4' x 4'
Puck mount: Up to 4' x 8'

MOUNTING
Lay-in grid, Adhesive, Pucks

FINISH*
White 1" and 2"
Silver, Pewter, Khaki and Black in 1" only

EDGES**
Square, 1/2" bevel available on 1" only (excludes Lay-in)
**Due to inconsistencies in the Melody core thickness, we recommend beveled edges or a 1/4" reveal between adjoining panels.

CLEANING
Bleach-Cleanable (10:1)
Water-Based/Solvent (WS)
Mold & Fungal Resistant (ASTM C1338)

SUSTAINABILITY
Declare, HPD, Indoor Advantage™ Gold

FLAMMABILITY
All components have a Class "A" rating per ASTM E84

*Also available in fabric wrapped (mTiles-Rap), and painted (mTiles-Canvas).

COLORS

| White 1" and 2" | Black 1" Only | Silver 1" Only | Pewter 1" Only | Khaki 1" Only |

Natural color variation may occur between panels due to the recycled content of the product, with Silver and Pewter being most susceptible to these variations.

Melody Declare.

CONTROLLING SOUND BEAUTIFULLY