Panel | Acoustic

Anchorage 2335



†Suitable for printing







Anchorage 2335

Panel | Acoustic

Specifications

Content	100% post-consumer recycled polyester
Weight	15.2 ± 1.0 oz./lin. yd
Width	66" min. useable
Repeat	none

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen perso

Miscellaneous

- · Application testing of this product is recommended.
- · Colors may vary between dye lots.

Proudly woven in North America supporting our local communities.

Sustainability

100% recycled and recyclable

a selection of timeless fabrics.



Renowned for its exceptional performance and style, Guilford of Maine has set industry standards in acoustics and panel fabrics for many decades. We present the Guilford of Maine Collection

Performance



Colorfastness to crocking (AATCC 8)
Grade 4 min. dry & Grade 3 min. wet

Breaking Strength (ASTM D5034)
275 lbf min. warp and fill



Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

Acoustic Transparency: 85

For more detailed results, please consult our website.



Certification Marks owned by the Association for Contract Textiles, In





